









## Dimmer List for LED Filament Bulbs

Brand	Photo	Model No.	Descriptions	Dimming Performance
		32E450UDM	Light Dimmer Mechanisms, 30 Series Standard Range, Dimmer Mechanism 250V 450W - Universal.	0~100% Dimming Range; Smooth, no flickering;
		32E450TM	A separately switched, compact, modular dimming mechanism rated at 450W (1.8A). The unit utilises state-of-the-art trailing edge dimming technology to provide full control of incandescent lighting and electronic transformer based low voltage lighting. Suitable for use in any new installation, but is also retro fittable, and may be used to replace a standard switch in any existing installation.	0~100% Dimming Range; Smooth, no flickering;
		32E450LM	Light Dimmer Mechanisms, 30 Series Standard Range, Dimmer Mechanism 250V 450W - Leading edge.	0~100% Dimming Range; Smooth, no flickering;
		Tillv.art.nr: CCTSE12011 Artikelnr: 1370640	Trend Transistordimmer Transistordimmer 20-315W, 20-630W och 40-1000W vriddimmer för ljusreglering av glödljus, 230V halogenlampor (R) och de flesta typer av elektroniska transformatorer (C), skruvanslutning. Till och frånslag via tryck på vred. Trappfunktion i kombination med strömställare. För infällt IP20 montage i apparatdosa c/c 60 eller för utanpå liggande montage 35mm dosa.	0~100% Dimming Range; Smooth, no flickering;
		Berker DRAAIDIMMER 2819 01	The mechanism of rotary dimmer 230V, 50Hz - Incandescent lamps and HV halogen lamps 60-400W, max. number of modules rozszarzenia power shined. 10 - Replacement fuse is possible without dismantling the central element, -with a rotary connector, - With smooth start saving lamps, - With protection against short circuit and overload (fuse) -with a spare, -adjustable by cutting phase, - With screw terminals	0~100% Dimming Range; Smooth, no flickering;

		<p>JQP401W</p>	<p>Varilight LED Dimmer Switch - V-Pro Series, 1 Gang (Single), 1 or 2 Way, 400 Watt (Trailing Edge)[Energy Class A+]</p>	<p>0~100% Dimming Range; Smooth, no flickering;</p>
		<p>AE Best.Nr.: 50.04.001</p>	<p>Dimmer 60-600W Typ: EHR 600W Wechsel (6mm) 230V~ F:M 3,15A</p>	<p>0~100% Dimming Range; Smooth, no flickering;</p>
		<p>E-nummer: E13 631 41 Art.nr: 3670 EAN: 7020160367006 Enhet: STK Färg: Fjällvit</p>	<p>Ohmsk last: 20-315W. 230V halogen: 20-300W. Elektronisk trafo: 20-315VA. IP-klass: 20. Anslutning: 2-ledare, vid trappkoppling 3- ledare. Spänning: 230V/50Hz. Säkring: Elektronisk. Brytare: Tryck, trapp. Koppling 6. Montagedjup: 25mm</p>	<p>0~100% Dimming Range; Smooth, no flickering;</p>
		<p>N.A.</p>	<p>100-240V, 50/60Hz, 3W-400W</p>	<p>0~100% Dimming Range; Smooth, no flickering;</p>
		<p>N.A.</p>	<p>100-240V, 50/60Hz, 20W-400W</p>	<p>0~100% Dimming Range; Smooth, no flickering;</p>

 <p>Members of the <b>OBI</b> Group</p>		<p>Art-Nr.: 400423</p>	<p>230-240V~, 50/60Hz, 20-300w. 1 gang 2way</p>	<p>0~100% Dimming Range; Smooth, no flickering;</p>
		<p>ZGRIDLED</p>	<ul style="list-style-type: none"> <li>•ZGRIDLED (5-250W LED)</li> <li>•MINIMUM LEVEL PRE SET LED / CFL LOADS</li> <li>•LEADING &amp; TRAILING EDGE TECHNOLOGY</li> <li>•8 GRID TOPS TO FIT ALL LEADING BRANDS</li> <li>•BLACK GRID TOPS AVAILABLE</li> </ul>	<p>0~100% Dimming Range; Smooth, no flickering;</p>
		<p>Retrotouch LED Rotary Dimmer Module 200W 2 Way</p>	<p>Rated Voltage: 100~240V AC 50/60Hz Operating Power: 6W - 200W (LED) Dimming Range: 3% - 100% Spindle height: 10mm Spindle Diameter: 6mm Measurement: 57mm x 23mm x 23mm</p>	<p>0~100% Dimming Range; Smooth, no flickering;</p>